

Wall Mounting & Floor Standing Enclosures


IP55 (IEC 529) Floor Standing Industrial Enclosures


- Polyurethane one piece gasket on door provides a continuous seal.
- Surface finished with epoxy powder coating.
- Double folded gutter at door frame to increase rigidity and to prevent water from entering while door is opened.
- Mounting plate adjustable in depth.
- Removable door rails ensure flexibility and rigidity.
- Extra C-rails welded at both sides of internal body to mount more accessories.
- For single Door Model, door is reversible for right or left opening.



Product Code	Dimension (mm) Height x Width x Depth	Mounting Brackets
R-CM148/40	1400 x 800 x 400	1
R-CM1410/40	1400 x 1000 x 400	2
R-CM168/40	1600 x 800 x 400	1
R-CM1610/40	1600 x 1000 x 400	2
R-CM1612/40	1600 x 1200 x 400	2
R-CM188/40	1800 x 800 x 400	1
R-CM1810/40	1800 x 1000 x 400	2
R-CM1812/40	1800 x 1200 x 400	2
R-CM208/40	2000 x 800 x 400	1
R-CM2010/40	2000 x 1000 x 400	2
R-CM2012/40	2000 x 1200 x 400	2

Optional Items

Canopies	Model	Enclosure Width	Enclosure Depth
	R-CPM8040	800mm	400mm
	R-CPM10030	1000mm	300mm
	R-CPM10040	1000mm	400mm
	R-CPM12040	1200mm	400mm

Plinths	Model	Enclosure Width	Enclosure Depth
	R-PL84/100	800mm	400mm
	R-PL103/100	1000mm	300mm
	R-PL104/100	1000mm	400mm
	R-PL124/100	1200mm	400mm

Height of all Plinths models at 100mm