

IP65 (IEC 529) Wall Mounting Stainless Steel Enclosures

- Made of stainless steel SS 304
- Hairline finished
- Enclosure body folded and welded from single piece material for maximum protection
- Polyurethane one piece gasket on door provides a continuous seal
- Conceal hinges provide 120° door opening
- Double folded gutter at door frame to increase rigidity and prevent water from entering while door is opened
- Earthing facilities on door, body and mounting plates.



Product Code	Dimension (mm) Height x Width x Depth	Die Cast Lock
R-CRX252015	250 x 200 x 150	1
R-CRX302515	300 x 250 x 150	1
R-CRX303015	300 x 300 x 150	1
R-CRX403015	400 x 300 x 150	1
R-CRX403020	400 x 300 x 200	1
R-CRX404020	400 x 400 x 200	1
R-CRX504020	500 x 400 x 200	2
R-CRX604020	600 x 400 x 200	2
R-CRX606025	600 x 600 x 250	2
R-CRX705025	700 x 500 x 250	2
R-CRX806025	800 x 600 x 250	2
R-CRX808030	800 x 800 x 300	2
R-CRX1008030	1000 x 800 x 300	2
R-CRX1208030	1200 x 800 x 300	2



Bridex Singapore Pte Ltd

a member of the **SMB** Group

47 Yishun Industrial Park A, Singapore 768724

Tel: 6756 0833 Fax: 6756 2007

<http://www.bridex.com.sg> e-mail: sales@bridex.com.sg

RUDOLF™ brandname is the registered trademark of Bridex Singapore Pte Ltd (a member of SMB United Group) in Singapore and other countries. Our policy is one of continuous development and we therefore reserve the right to alter technical data without prior notice.

Note:

1. All the above items are complete with base plate.
2. Base plate is made of zinc plated mild steel sheet.
3. Without gland opening and gland plate.
4. Optional item - stainless steel wall mounting brackets.