

HRC Cylindrical Fuse

Application

Protection and control of circuits against overloads and short circuits:

- in domestic installations
- in commercial and light industrial electrical distribution

Technical data

Standard comply to: IEC 269, VDE 0636

Rated Breaking Capacity: 120kA - 500Vac

3 sizes: 10x38, 14x51 and 22x58

Ratings from: 1A to 100A

2 application categories at 500V AC

- GL (distribution)
- AM (motor)

Description	Rating/A	GL Type Ref. No.	AM Type Ref. No.
10 x 38mm Cylindrical Fuse	1	LX001	MX001
	2	LX002	MX002
	4	LX004	MX004
	6	LX006	MX006
	8	LX008	MX008
	10	LX010	MX010
	12	LX012	MX012
	16	LX016	MX016
	20	LX020	MX020
	25	LX025	MX025
	32	LX032	MX032



LX032

14 x 51mm Cylindrical Fuse	4	LY004	MY004
	6	LY006	MY006
	10	LY010	MY010
	16	LY016	MY016
	20	LY020	MY020
	25	LY025	MY025
	32	LY032	MY032
	40	LY040	MY040
	50	LY050	MY050



LY050

22 x 58mm Cylindrical Fuse	32	LZ032	MZ032
	40	LZ040	MZ040
	50	LZ050	MZ050
	63	LZ063	MZ063
	80	LZ080	MZ080
	100	LZ100	MZ100

