

## Ordering Format

R-DSS - □□□ - □□ - □□

R-DSSi - □□□ - □□ - □□

Control Supply (A1, A2, A3)

C1	110~240 VAC & 380~440 VAC
C2	24 VAC/VDC

Mains Supply (L1, L2, L3)

V4	3Ø, 200~400 VAC, 45-66 Hz
V6	3Ø, 200~575 VAC, 45-66 Hz

Product Code	kW@ 400V
R-DSS-007 / R-DSSi-007	7.5kW
R-DSS-015 / R-DSSi-015	15kW
R-DSS-018 / R-DSSi-018	18.5kW
R-DSS-022 / R-DSSi-022	22kW
R-DSS-030 / R-DSSi-030	30kW
R-DSS-037 / R-DSSi-037	37kW
R-DSS-045 / R-DSSi-045	45kW
R-DSS-055 / R-DSSi-055	55kW
R-DSS-075 / R-DSSi-075	75kW
R-DSS-090 / R-DSSi-090	90kW
R-DSS-110 / R-DSSi-110	110kW

## Selection Guide

Product Code	Starter Rating				Dimension (mm)		
	AC53b 4-6:354	AC53b 4-20:340	AC53b 4~6:594	AC53b 4~20:580	Height	Width	Depth
R-DSS-007-V4-C1 / R-DSSi-007-V4-C1	18A	17A			203	98	165
R-DSS-015-V4-C1 / R-DSSi-015-V4-C1	34A	30A			203	98	165
R-DSS-018-V4-C1 / R-DSSi-018-V4-C1	42A	36A			203	98	165
R-DSS-022-V4-C1 / R-DSSi-022-V4-C1	48A	40A			203	98	165
R-DSS-030-V4-C1 / R-DSSi-030-V4-C1	60A	49A			203	98	165
R-DSS-037-V4-C1 / R-DSSi-037-V4-C1			75A	65A	215	145	193
R-DSS-045-V4-C1 / R-DSSi-045-V4-C1			85A	73A	215	145	193
R-DSS-055-V4-C1 / R-DSSi-055-V4-C1			100A	96A	215	145	193
R-DSS-075-V4-C1 / R-DSSi-075-V4-C1			140A	120A	240	202	214
R-DSS-090-V4-C1 / R-DSSi-090-V4-C1			170A	142A	240	202	214
R-DSS-110-V4-C1 / R-DSSi-110-V4-C1			200A	165A	240	202	214