

Motor Ratings

Continuous Ratings

MODEL	Normal Duty 3.0 x FLC AC53a 3-10:50-10 45°C < 1000 metres		Heavy Duty 3.5 x FLC AC53a 3.5-15:50-10 45°C < 1000 metres	
	3 wire	6 wire	3 wire	6 wire
IMS2-0018	18A	27A	16A	25A
IMS2-0034	34A	51A	32A	48A
IMS2-0041	41A	62A	39A	58A
IMS2-0047	47A	71A	44A	66A
IMS2-0067	67A	101A	60A	90A
IMS2-0088	88A	132A	78A	116A
IMS2-0096	96A	144A	85A	127A
IMS2-0125	125A	188A	112A	168A
IMS2-0141	141A	212A	122A	183A
IMS2-0202	202A	303A	177A	266A
IMS2-0238	238A	357A	211A	317A
IMS2-0253	253A	379A	218A	327A
IMS2-0302	302A	453A	275A	413A
IMS2-0405	405A	608A	376A	564A
IMS2-0513	513A	769A	481A	722A
IMS2-0585	585A	878A	558A	837A
IMS2-0628	628A	942A	595A	893A
IMS2-0775	775A	1163A	756A	1134A
IMS2-0897	897A	1346A	895A	1342A
IMS2-1153	1153A	1730A	1049A	1574A
IMS2-1403	1403A	2105A	1302A	1953A
IMS2-1574	1574A	2361A	1486A	2229A

Bypassed Ratings

MODEL	Normal Duty 3.0 x FLC AC53b 3-10:350 45°C < 1000 metres		Heavy Duty 3.5 x FLC AC53b 3.5-15:345 45°C < 1000 metres	
	3 wire	6 wire	3 wire	6 wire
IMS2-0018	18A	27A	18A	27A
IMS2-0034	34A	51A	34A	51A
IMS2-0041	41A	62A	41A	62A
IMS2-0047	47A	71A	47A	71A
IMS2-0067	67A	101A	62A	94A
IMS2-0088	88A	132A	82A	122A
IMS2-0096	96A	144A	90A	136A
IMS2-0125	125A	188A	120A	181A
IMS2-0141	141A	212A	127A	190A
IMS2-0202	202A	303A	187A	281A
IMS2-0238	238A	357A	224A	336A
IMS2-0253	254A	381A	228A	342A
IMS2-0302	302A	453A	285A	427A
IMS2-0405	405A	608A	395A	592A
IMS2-0513	513A	770A	513A	770A
IMS2-0585	585A	878A	585A	878A
IMS2-0628	628A	942A	626A	939A
IMS2-0775	775A	1163A	775A	1163A
IMS2-0897	897A	1346A	897A	1346A
IMS2-1153	1153A	1730A	1153A	1730A
IMS2-1403	1403A	2105A	1403A	2105A
IMS2-1574	1574A	2361A	1574A	2361A

Part Number Format

